

Ni-Cd Cylindrical Rechargeable Battery Cells

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Standard Charge		Rapid Charge		Approx Weight (g)
				Diameter (mm)	Height (mm)	Current (mA)	Time (h)	Current (mA)	Time (h)	
AAA	EJD-1/3AAA60	1.2	60	10.5	14.5	6	16	60	1.5	4
AAA	EJD-2/3AAA200	1.2	200	10.5	29.0	20	16	200	1.5	6
AAA	EJD-2/3AAA250	1.2	250	10.5	29.0	25	16	250	1.5	6
AAA	EJD-AAA200	1.2	200	10.5	44.5	20	16	200	1.5	7.5
AAA	EJD-AAA250	1.2	250	10.5	44.5	25	16	250	1.5	11
AAA	EJD-AAA300	1.2	300	10.5	44.5	30	16	300	1.5	12
AAA	EJD-AAA350	1.2	350	10.5	44.5	35	16	350	1.5	13
AAA	EJD-AAA400	1.2	400	10.5	44.5	40	16	400	1.5	13
AA	EJD-1/3AA180	1.2	180	14.5	17.0	18	16	180	1.5	8
AA	EJD-2/3AA300	1.2	300	14.5	29.0	30	16	300	1.5	13
AA	EJD-2/3AA350	1.2	350	14.5	29.0	35	16	350	1.5	13.5
AA	EJD-2/3AA400	1.2	400	14.5	29.0	40	16	400	1.5	14
AA	EJD-4/5AA600	1.2	600	14.5	43.0	60	16	600	1.5	20
AA	EJD-4/5AA700	1.2	700	14.5	43.0	70	16	700	1.5	20
AA	EJD-AA600	1.2	600	14.5	50.5	60	16	600	1.5	22
AA	EJD-AA700	1.2	700	14.5	50.5	70	16	700	1.5	22
AA	EJD-AA800	1.2	800	14.5	50.5	80	16	800	1.5	23
AA	EJD-AA900	1.2	900	14.5	50.5	90	16	900	1.5	24
AA	EJD-AA1000	1.2	1000	14.5	50.5	100	16	1000	1.5	24
AA	EJD-AA1100	1.2	1100	14.5	50.5	110	16	1100	1.5	24
AA	EJD-4/3AA1100	1.2	1100	14.5	65.5	110	16	1100	1.5	30
AA	EJD-4/3AA1200	1.2	1200	14.5	65.5	120	16	1200	1.5	31
A	EJD-2/3A600	1.2	600	17.0	28.0	60	16	600	1.5	20
A	EJD-2/3A700	1.2	700	17.0	28.0	70	16	700	1.5	20
A	EJD-4/5A1100	1.2	1100	17.0	43.0	110	16	1100	1.5	27
A	EJD-4/5A1200	1.2	1200	17.0	43.0	120	16	1200	1.5	27
A	EJD-7/5A1800	1.2	1800	17.0	66	180	16	1800	1.5	—
A	EJD-7/5A2000	1.2	2000	17.0	66	200	16	2000	1.5	—
A	EJD-A1200	1.2	1200	17.0	50.0	120	16	1200	1.5	32
A	EJD-A1300	1.2	1300	17.0	50.0	130	16	1300	1.5	32
A	EJD-A1400	1.2	1400	17.0	50.0	140	16	1400	1.5	32
A	EJD-A1500	1.2	1500	17.0	50.0	150	16	1500	1.5	34
SC	EJD-12SC850	1.2	850	23.0	25.5	85	16	700	1.5	25
SC	EJD-2/3SC700	1.2	700	23.0	26.5	70	16	700	1.5	28
SC	EJD-4/5SC1100	1.2	1100	23.0	34.0	110	16	1100	1.5	40
SC	EJD-4/5SC1200	1.2	1200	23.0	34.0	120	16	1200	1.5	41
SC	EJD-5/4SC2000	1.2	2000	23.0	49	200	16	2000	1.5	—
SC	EJD-5/4SC2300	1.2	2300	23.0	49	230	16	2300	1.5	—
SC	EJD-SC1300	1.2	1300	23.0	43.0	130	16	1300	1.5	48
SC	EJD-SC1500	1.2	1500	23.0	43.0	150	16	1500	1.5	49
SC	EJD-SC1700	1.2	1700	23.0	43.0	170	16	1700	1.5	49
SC	EJD-SC1800	1.2	1800	23.0	43.0	180	16	1800	1.5	49

SC	EJD-SC1900	1.2	1900	23.0	43.0	190	16	1900	1.5	50
SC	EJD-SC2000	1.2	2000	23.0	43.0	200	16	2000	1.5	50
SC	EJD-SC2100	1.2	2100	23.0	43.0	210	16	2100	1.5	50
SC	EJD-SC2200	1.2	2200	23.0	43.0	220	16	2200	1.5	51
C	EJD-1/2C750	1.2	750	25.8	25.5	75	16	750	1.5	—
C	EJD-2/3C1100	1.2	1100	25.8	28.5	110	16	1100	1.5	—
C	EJD-C1200	1.2	1200	25.8	51.0	120	16	1200	1.5	53
C	EJD-C1500	1.2	1500	25.8	51.0	150	16	1500	1.5	56
C	EJD-C2000	1.2	2000	25.8	51.0	200	16	2000	1.5	65
C	EJD-C2500	1.2	2500	25.8	51.0	250	16	2500	1.5	70
C	EJD-C2800	1.2	2800	25.8	51.0	280	16	2800	1.5	73
C	EJD-C3000	1.2	3000	25.8	51.0	300	16	3000	1.5	75
D	EJD-1/2D2200	1.2	2200	33.0	36.5	220	16	2200	1.5	75
D	EJD-1/2D2300	1.2	2300	33.0	36.5	230	16	2300	1.5	76
D	EJD-D1200	1.2	1200	33.0	61.5	120	16	1200	1.5	66
D	EJD-D1500	1.2	1500	33.0	61.5	150	16	1500	1.5	66
D	EJD-D4000	1.2	4000	33.0	61.5	400	16	4000	1.5	135
D	EJD-D4500	1.2	4500	33.0	61.5	450	16	4500	1.5	140
D	EJD-D5000	1.2	5000	33.0	61.5	500	16	5000	1.5	145
D	EJD-D5500	1.2	5500	33.0	61.5	550	16	5500	1.5	150
F	EJD-F7000	1.2	7000	33.0	90.5	700	16	7000	1.5	195
F	EJD-F8000	1.2	8000	33.0	90.5	900	16	8000	1.5	200
F	EJD-F9000	1.2	9000	33.3	90.5	900	16	9000	1.5	210
N	EJD-N180	1.2	180	12.0	30.0	18	16	180	1.5	8

Ni-Cd 9V Rechargeable Battery Cells

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions T*W*H (mm)	Standard Charge		Rapid Charge		Approx Weight (g)
					Current (mA)	Time (h)	Current (mA)	Time (h)	
6F22(9.6V)	9V 100	9.0	100	17.5X26.5X48.5	10	16	100	1.5	42
6F22(9.6V)	9V 120	9.0	120	17.5X26.5X48.5	12	16	120	1.5	42

Ni-Cd Button Battery Cells

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Standard Charge		Discharging	Approx Weight (g)
			Diameter (mm)	Height (mm)	Current (mA)	Time (h)		
15K	1.2	15	11.4	3.1	1.5	15	3mA / 1.0V	1.2
30K	1.2	30	11.5	5.4	3.0	15	6mA / 1.0V	2.2
60K	1.2	60	15.2	6.0	6.0	15	12mA / 1.0V	3.0
100K	1.2	100	15.2	7.9	10	15	20mA / 1.0V	3.5
120K	1.2	120	23.3L X 15.0W	5.0	12	15	24mA / 1.0V	5.0
170K	1.2	170	25.0	6.2	17	15	34mA / 1.0V	9.6
280K	1.2	280	25.0	8.8	28	15	56mA / 1.0V	12.5
450K	1.2	450	34.0L X 24.0W	5.5	45	15	12mA / 1.0V	13.5

High Drain Ni-CD Battery Cells

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Standard Charge		Rapid Charge		Approx Weight (g)
				Diameter (mm)	Height (mm)	Current (mA)	Time (h)	Current (mA)	Time (h)	
AAA	EJD-AAA300P	1.2	300	43	10.2	60	7.5	300	1.2	—
2/3AA	EJD-AA300P	1.2	300	28.5	14.1	60	7.5	300	1.2	—
AA	EJD-AA700P	1.2	700	49.5	14.1	140	7.5	700	1.2	22
AA	EJD-AA900P	1.2	900	49.5	14.1	180	7.5	900	1.2	24
2/3A	EJD-A650P	1.2	650	28.5	17	130	7.5	650	1.2	—
SC	EJD-SC1300P	1.2	1300	42	22.1	260	7.5	1300	1.2	46
SC	EJD-SC1500P	1.2	1500	42	22.1	300	7.5	1500	1.2	46
SC	EJD-SC1800P	1.2	1800	42	22.1	360	7.5	1800	1.2	48
C	EJD-C2200P	1.2	2200	49	25.3	440	7.5	2200	1.2	70
C	EJD-C2500P	1.2	2500	49	25.3	500	7.5	2500	1.2	72
D	EJD-D4500P	1.2	4500	59	32.3	900	7.5	4500	1.2	126
D	EJD-D5000P	1.2	5000	59	32.3	1000	7.5	5000	1.2	130
F	EJD-F7500P	1.2	7500	89	32.3	1400	7.5	7500	1.2	190

High Temperature Ni-CD Battery Cells

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Remark
				Diameter (mm)	Height (mm)	
AA	EJD-AA600HT	1.2	600	48	13.9	1) HT: High temperature battery. 2) High recharge-discharge temperature: 70°C. 3) Float recharge life: 4 year.
AA	EJD-AA800HT	1.2	800	48	13.9	
SC	EJD-SC1300HT	1.2	1300	42	22	
SC	EJD-SC1500HT	1.2	1500	42	22	
SC	EJD-SC1800HT	1.2	1800	42	22	
C	EJD-C2200HT	1.2	2200	49	25.2	
C	EJD-C2500HT	1.2	2500	49.5	25.2	
C	EJD-C3000HT	1.2	3000	49.5	25.2	
D	EJD-D4000HT	1.2	4000	59	32.1	

Low Temperature Ni-CD Battery Cells

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Remark
				Diameter (mm)	Height (mm)	
AA	EJD-AA700LH	1.2	700	49.5	14.1	1) LT: Low temperature battery.
AA	EJD-AA800LH	1.2	800	49.5	14.1	
AA	EJD-AA900LH	1.2	900	49.5	14.1	
SC	EJD-SC1500LH	1.2	1500	42	22.1	