

### Cylindrical LiFePO4 Li-ion Batteries

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension		Standard Charge current (mA)	Rapid Charge current (mA)	Weight approx(g)
			Diameter (mm)	Height (mm)			
IFR10130	3.2	30	10.3	13.2	6	30	5
IFR10440	3.2	200	10.3	44.2	40	200	7
IFR14430	3.2	250	10.3	43	50	250	11
IFR14430	3.2	300	10.3	43	60	300	12
IFR14430	3.2	400	14	43	80	400	13
IFR14500	3.2	250	14	50.5	50	250	14
IFR14500	3.2	400	14	50.5	80	400	15.5
IFR14500	3.2	500	14	50.5	100	500	16
IFR14500	3.2	600	14	50.5	120	600	18
IFR14650	3.2	800	14	65.5	160	800	21
IFR15270	3.2	200	15.2	27	40	200	10
IFR16340	3.2	300	16.2	34.2	60	300	13.5
IFR16340	3.2	400	16.2	34.2	80	400	15
IFR17335	3.2	450	16.5	33.5	90	450	15
IFR18500	3.2	1000	18.5	50.2	200	1000	32
IFR18500	3.2	600	18.5	50.2	120	600	26
IFR18500	3.2	450	18.5	50.2	90	450	28
IFR18500	3.2	900	18.5	50.2	180	900	30
IFR18650	3.2	1200	18.5	65.5	240	1200	40
IFR18650	3.2	1300	18.5	65.5	260	1300	41
IFR18650	3.2	1400	18.5	65.5	280	1400	42
IFR18650	3.2	1500	18.5	65.5	300	1500	42
IFR22430	3.2	1100	22.5	43.3	220	1100	45
IFR22430	3.2	1200	22.5	43.3	240	1200	47
IFR22650	3.2	1800	22.5	65.5	360	1800	60
IFR22650	3.2	1900	22.5	65.5	380	1900	62
IFR22650	3.2	2000	22.5	65.5	400	2000	63
IFR26650	3.2	2700	26.5	65.5	540	2700	80
IFR26650	3.2	2900	22.5	65.5	580	2900	83
IFR26650	3.2	3000	22.5	65.5	600	3000	85
IFR26650	3.2	3100	22.5	65.5	620	3100	86
IFR26650	3.2	3200	22.5	65.5	640	3200	88
IFR26650	3.2	3300	22.5	65.5	660	3300	90
IFR32600	3.2	3500	32.5	60.5	700	3500	125
IFR32600	3.2	3600	32.5	60.5	720	3600	129
IFR32650	3.2	4200	32.5	65.5	840	4200	135

IFR32650	3.2	4500	32.5	65.5	900	4500	135
IFR32900	3.2	4500	32.5	90.5	900	4500	170
IFR32900	3.2	5000	32.5	90.5	1000	5000	180
IFR32900	3.2	5500	32.5	90.5	1100	5500	192
IFR42110	3.2	10000	42.5	110.5	2000	10000	350
IFR42110	3.2	11000	42.5	110.5	2200	11000	360
IFR42120	3.2	11000	42.5	120.5	2200	11000	360
IFR42120	3.2	12000	42.5	120.5	2400	12000	380
IFR42120	3.2	13000	42.5	120.5	2600	13000	390

## High Power Cylindrical LiFePO4 Li-ion Batteries

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension		Standard Charge current (mA)	Rapid Charge current (mA)	Weight approx(g)
			Diameter (mm)	Height (mm)			
IFR18650-10C	3.2	1100	18.5	65.5	220	2200	40
IFR18650-15C	3.2	1000	18.5	65.5	200	2000	40
IFR26650-10C	3.2	2400	26.5	65.5	480	4800	82
IFR26650-20C	3.2	2100	26.5	65.5	420	4200	82
IFR32650-5C	3.2	3800	32.5	65.5	760	7600	135
IFR32650-10C	3.2	3500	32.5	65.5	700	7000	135
IFR32650-10C	3.2	3800	32.5	65.5	760	7600	135
IFR32900-5C	3.2	5500	32.5	90.5	1100	11000	180