

## Ni-Cd Cylindrical Rechargeable Batteries

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension With Tube		Standard Charge		Rapid Charge		Weight Approx (g)
				Diameter (mm)	Height (mm)	Current (mA)	Time (h)	Current (mA)	Time (h)	
AAA	EJD-1/3AAA60	1.2	60	10.5	14.5	6	15	60	1.4	4
	EJD-2/3AAA200	1.2	200	10.5	29.0	20	15	200	1.4	6
	EJD-2/3AAA250	1.2	250	10.5	29.0	25	15	250	1.4	6
	EJD-AAA200	1.2	200	10.5	44.5	20	15	200	1.4	7.5
	EJD-AAA250	1.2	250	10.5	44.5	25	15	250	1.4	11
	EJD-AAA300	1.2	300	10.5	44.5	30	15	300	1.4	12
	EJD-AAA350	1.2	350	10.5	44.5	35	15	350	1.4	13
AA	EJD-1/3AA180	1.2	180	14.5	17.0	18	15	180	1.4	8
	EJD-2/3AA300	1.2	300	14.5	29.0	30	15	300	1.4	13
	EJD-2/3AA350	1.2	350	14.5	29.0	35	15	350	1.4	13.5
	EJD-2/3AA400	1.2	400	14.5	29.0	40	15	400	1.4	14
	EJD-4/5AA600	1.2	600	14.5	43.0	60	15	600	1.4	20
	EJD-4/5AA700	1.2	700	14.5	43.0	70	15	700	1.4	20
	EJD-AA600	1.2	600	14.5	50.5	60	15	600	1.4	22
	EJD-AA700	1.2	700	14.5	50.5	70	15	700	1.4	22
	EJD-AA800	1.2	800	14.5	50.5	80	15	800	1.4	23
	EJD-AA900	1.2	900	14.5	50.5	90	15	900	1.4	24
	EJD-AA1000	1.2	1000	14.5	50.5	100	15	1000	1.4	24
	EJD-AA1100	1.2	1100	14.5	50.5	110	15	1100	1.4	24
	EJD-4/3AA1100	1.2	1100	14.5	65.5	110	15	1100	1.4	30
	EJD-4/3AA1200	1.2	1200	14.5	65.5	120	15	1200	1.4	31
A	EJD-2/3A600	1.2	600	17.0	28.0	60	15	600	1.4	20
	EJD-2/3A700	1.2	700	17.0	28.0	70	15	700	1.4	20
	EJD-4/5A1100	1.2	1100	17.0	43.0	110	15	1100	1.4	27
	EJD-4/5A1200	1.2	1200	17.0	43.0	120	15	1200	1.4	27
	EJD-7/5A1800	1.2	1800	17.0	66	180	15	1800	1.4	—
	EJD-7/5A2000	1.2	2000	17.0	66	200	15	2000	1.4	—
	EJD-A1200	1.2	1200	17.0	50.0	120	15	1200	1.4	32
	EJD-A1300	1.2	1300	17.0	50.0	130	15	1300	1.4	32
	EJD-A1400	1.2	1400	17.0	50.0	140	15	1400	1.4	32
	EJD-A1500	1.2	1500	17.0	50.0	150	15	1500	1.4	34
SC	EJD-12SC850	1.2	850	23.0	25.5	85	15	700	1.4	25
	EJD-2/3SC700	1.2	700	23.0	26.5	70	15	700	1.4	28
	EJD-4/5SC1100	1.2	1100	23.0	34.0	110	15	1100	1.4	40
	EJD-4/5SC1200	1.2	1200	23.0	34.0	120	15	1200	1.4	41
	EJD-5/4SC2000	1.2	2000	23.0	49	200	15	2000	1.4	—
	EJD-5/4SC2300	1.2	2300	23.0	49	230	15	2300	1.4	—
	EJD-SC1300	1.2	1300	23.0	43.0	130	15	1300	1.4	48
	EJD-SC1500	1.2	1500	23.0	43.0	150	15	1500	1.4	49
	EJD-SC1700	1.2	1700	23.0	43.0	170	15	1700	1.4	49
	EJD-SC1800	1.2	1800	23.0	43.0	180	15	1800	1.4	49
	EJD-SC1900	1.2	1900	23.0	43.0	190	15	1900	1.4	50
	EJD-SC2000	1.2	2000	23.0	43.0	200	15	2000	1.4	50
	EJD-SC2100	1.2	2100	23.0	43.0	210	15	2100	1.4	50
	EJD-SC2200	1.2	2200	23.0	43.0	220	15	2200	1.4	51

C	EJD-1/2C750	1.2	750	25.8	25.5	75	15	750	1.4	—
	EJD-2/3C1100	1.2	1100	25.8	28.5	110	15	1100	1.4	—
	EJD-C1200	1.2	1200	25.8	51.0	120	15	1200	1.4	53
	EJD-C1500	1.2	1500	25.8	51.0	150	15	1500	1.4	56
	EJD-C2000	1.2	2000	25.8	51.0	200	15	2000	1.4	65
	EJD-C2500	1.2	2500	25.8	51.0	250	15	2500	1.4	70
	EJD-C2800	1.2	2800	25.8	51.0	280	15	2800	1.4	73
	EJD-C3000	1.2	3000	25.8	51.0	300	15	3000	1.4	75
D	EJD-1/2D2200	1.2	2200	33.0	36.5	220	15	2200	1.4	75
	EJD-1/2D2300	1.2	2300	33.0	36.5	230	15	2300	1.4	76
	EJD-D1200	1.2	1200	33.0	61.5	120	15	1200	1.4	66
	EJD-D1500	1.2	1500	33.0	61.5	150	15	1500	1.4	66
	EJD-D4000	1.2	4000	33.0	61.5	400	15	4000	1.4	135
	EJD-D4500	1.2	4500	33.0	61.5	450	15	4500	1.4	140
	EJD-D5000	1.2	5000	33.0	61.5	500	15	5000	1.4	145
	EJD-D5500	1.2	5500	33.0	61.5	550	15	5500	1.4	150
F	EJD-F7000	1.2	7000	33.0	90.5	700	15	7000	1.4	195
	EJD-F8000	1.2	8000	33.0	90.5	900	15	8000	1.4	200
	EJD-F9000	1.2	9000	33.3	90.5	900	15	9000	1.4	210
N	EJD-N180	1.2	180	12.0	30.0	18	15	180	1.4	8

### Ni-Cd 9V Rechargeable Batteries

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension With Tube	Standard Charge		Rapid Charge		Weight Approx (g)
				T*W*H (mm)	Current (mA)	Time (h)	Current (mA)	Time (h)	
6F22(9.6V)	9V 100	9.0	100	17.5X26.5X48.5	10	15	100	1.4	42
6F22(9.6V)	9V 120	9.0	120	17.5X26.5X48.5	12	15	120	1.4	42

### Ni-Cd Button Cell

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimension With Tube		Standard Charge		Discharging	Weight Approx (g)
			Diameter (mm)	Height (mm)	Current (mA)	Time (h)		
15K	1.2	15	11.4	3.1	1.5	15	3mA / 1.0V	1.2
30K	1.2	30	11.5	5.4	3.0	15	6mA / 1.0V	2.2
60K	1.2	60	15.2	6.0	6.0	15	12mA / 1.0V	3.0
100K	1.2	100	15.2	7.9	10	15	20mA / 1.0V	3.5
120K	1.2	120	23.3L X 15.0W	5.0	12	15	24mA / 1.0V	5.0
170K	1.2	170	25.0	6.2	17	15	34mA / 1.0V	9.6
280K	1.2	280	25.0	8.8	28	15	56mA / 1.0V	12.5
450K	1.2	450	34.0L X 24.0W	5.5	45	15	12mA / 1.0V	13.5